

**POWER SUPPLY UNIT
BP-2I**

PASSPORT

- Connect the wires to the shoe according to the supply voltage and the current consumption of your product.
- Connect the unit to the AC mains 220V through the circuit breaker.

5. WARRANTY LIABILITIES

The manufacturer guarantees the compliance of the METACOM BP-2I power supply unit with the requirements of MTCM.430600.001 TU when the consumer applies the rules of use, storage and transportation.

The warranty period for the operation of the product is 12 months from the date of sale, but not more than 18 months from the date of manufacture.

The service life of the product is 5 years from the date of manufacture.

In the presence of mechanical, electrical or other types of damage caused by improper transportation, storage, operation or actions of third parties, no claims for quality are accepted and no warranty repair is performed.

6. CERTIFICATE OF ACCEPTANCE

The METAKOM BP-2I feeder unit meets the technical requirements and is recognized as suitable for operation.

Release date _____

OTK representative _____

seal

The address of the manufacturer: Russia, 241024,
Bryansk, Delegate str., 68, LLC "Metacom"
tel./fax: (4832) 68-28-26
Tel. (4832) 68-28-25
http:// www.metakom-plus.ru
E-mail: os@metakom-plus.ru



The product is certified

1. PURPOSE

The power supply unit **METAKOM BP-2I** is intended for powering the intercom systems and additional equipment manufactured by Metacom. The unit is powered by an alternating current network with a voltage of 160 ... 242 V at a frequency of 50 Hz. The unit can be operated in the temperature range from -20 to +40 ° C with a relative air humidity of not more than 95%.

The power supply unit is protected against short circuit on the input and protection against overload on each of the outputs.

2. SPECIFICATIONS

Specifications	BP-2I
Voltage of AC mains, V	160...242
Output voltage of the first channel, V	17±0,2
Maximum load current of the first channel, A	0,8
Output voltage of the second channel, V	13,2±0,3
Maximum load current of the second channel, A	1,2
Power consumption from the network at the rated supply voltage and the maximum load current, not more than, W	43
Overall dimensions (without cord), mm	160x85x40
Weight, not more than, kg	0,4

3. CONTENTS OF DELIVERY

Power supply unit BP-2I	1 pcs.
Passport	1 pcs.
Individual packing	1 pcs.

4. PREPARATION AND OPERATION PROCEDURE

- The power supply unit mustn't be exposed to dripping or splashing of liquids.

